

2013

F-150 and F-150 SVT Raptor Weight Ratings cont'd

F-150 Styleside Pickup — GVWR/Payload/OPT & ARC/GAWR (Front Computer-Selected)/Base Curb Weight

Cab Style/ Drive/WB (in.)	Engine	Max. GVWR (lbs.)	Max. Payload (lbs.) ⁽¹⁾	OPT/ARC Weight (lbs.) ⁽²⁾	Max. GAWR (lbs.) ⁽³⁾		Base Curb Weight (lbs.)		
					Front	Rear ⁽⁴⁾	Front	Rear	Total
Regular Cab 4x2 126	3.7L	6450	1710	714	3150	3500	2675	2010	4685
	5.0L	6650	1810	708	3300	3500	2771	2020	4791
Regular Cab 4x4 126	3.7L	6650	1670	781	3450	3500	2905	2020	4925
	5.0L	6800	1710	773	3450	3500	2994	2039	5033
Regular Cab 4x2 145	3.7L	6750	1930	1050	3450	3800	2782	1982	4764
	5.0L	7050	2090	1050	3450	3850	2891	2010	4901
	3.5L	7050	2060	990	3600	3850	2948	1987	4935
HD Pkg.	3.5L	8200	3100	929	3750	4800	2969	2114	5083
	5.0L	8200	3120	989	3750	4800	2969	2094	5063
Regular Cab 4x4 145	3.7L	6950	1900	1090	3600	3800	3008	1985	4993
	5.0L	7250	2060	1086	3750	3850	3107	2023	5130
	3.5L	7200	1920	1026	3750	3850	3137	2083	5220
HD Pkg.	3.5L	8200	2810	968	4050	4800	3175	2192	5367
	5.0L	8200	2810	968	4050	4800	3203	2165	5368
SuperCab 4x4 133 SVT Raptor	6.2L	7050	980	205	3900	3500	3414	2590	6004
SuperCab 4x2 145	3.7L	6700	1600	737	3450	3800	2884	2159	5043
	5.0L	7100	1870	934	3750	3850	2983	2186	5169
	3.5L	7050	1790	926	3750	3850	2996	2207	5203
	6.2L	7500	2010	837	3750	4050	3122	2312	5434
MAX	3.5L	7500	2080	758	3750	4050	3043	2323	5366
SuperCab 4x4 145	3.7L	6900	1510	647	3750	3800	3126	2207	5333
	5.0L	7350	1830	969	3900	3850	3222	2239	5461
	3.5L	7200	1660	804	3900	3850	3204	2272	5476
MAX	3.5L	7700	2000	821	3900	4050	3253	2383	5636
	6.2L	7700	1950	867	4050	4050	3356	2333	5689
SuperCab 4x2 163	5.0L	7300	1930	1068	3900	3850	3110	2202	5312
	3.5L	7300	1920	1063	3900	3850	3110	2207	5317
MAX	3.5L	7550	1990	926	3900	4050	3162	2337	5499
HD Pkg.	5.0L	8200	2710	1024	4050	4800	3159	2310	5469
	3.5L	8200	2700	964	4050	4800	3159	2315	5474
SuperCab 4x4 163	5.0L	7450	1770	910	4050	3850	3309	2311	5620
	3.5L	7450	1780	926	4050	3850	3299	2305	5604
MAX	3.5L	7700	1860	989	4050	4050	3348	2426	5774
HD Pkg.	5.0L	8200	2400	998	4050	4800	3378	2399	5777
	3.5L	8200	2390	998	4050	4800	3348	2437	5785
SuperCrew 4x2 145	3.7L	6800	1620	656	3450	3800	2885	2243	5128
	5.0L	7100	1790	879	3600	3850	2963	2291	5254
	3.5L	7100	1750	871	3600	3850	2989	2307	5296
	3.5L GTDI	7100	1480	597	3600	3850	3114	2444	5558
	6.2L	7250	1480	597	3600	3850	3198	2512	5710
MAX	3.5L	7400	1930	751	3600	4050	3006	2401	5407
	6.2L	7400	1810	807	3750	4050	3107	2423	5530

(1) Load rating represents maximum allowable weight of people, cargo and body equipment and is reduced by optional equipment weight.

(2) OPT/ARC Weight is the maximum allowable weight for regular production options (OPT) and aftermarket equipment. Accessory Reserve Capacity (ARC) for models with standard equipment and the engine/transmission combination indicated.

(3) Gross Axle Weight Rating (GAWR) is determined by the rated capacity of the minimum component of the axle system (axle, computer-selected springs, wheels, tires) of a specific vehicle. Front and rear GAWRs will, in all cases, sum to a number equal to or greater than the GVWR for the particular vehicle. Maximum loaded vehicle (including passengers, equipment and payload) cannot exceed the GVWR.

(4) Vehicles equipped with 20" tires/wheels get 4050 lbs. RGAWR.

NOTE: Refer to pages 94 and 95 for Standard Powertrain/Chassis Equipment Specifications. See the Truck Payload section in the Source Book Appendices or on eSourceBook for optional equipment weights.

F-150 and F-150 SVT Raptor

Weight Ratings cont'd

2013

F-150 and
F-150 SVT Raptor

F-150 Styleside Pickup — GVWR/Payload/OPT & ARC/GAWR (Front Computer-Selected)/Base Curb Weight

Cab Style/ Drive/WB (in.)	Engine	Max. GVWR (lbs.)	Max. Payload (lbs.) ⁽¹⁾	OPT/ARC Weight (lbs.) ⁽²⁾	Max. GAWR (lbs.) ⁽³⁾		Base Curb Weight (lbs.)		
					Front	Rear ⁽⁴⁾	Front	Rear	Total
SuperCrew 4x4 145	5.0L	7350	1700	844	3900	3850	3214	2372	5586
	3.5L	7200	1520	665	3900	3850	3206	2409	5615
	3.5L	7200	1300	595	3750	3850	3317	2518	5835
SVT Raptor MAX	6.2L	7350	1370	631	3850	3850	3393	2524	5917
	6.2L	7450	1120	477	4000	3700	3459	2654	6203
	3.5L	7650	1900	814	3900	4050	3206	2481	5687
SuperCrew 4x2 157	6.2L	7700	1860	829	4050	4050	3324	2450	5774
	5.0L	7100	1700	835	3750	3850	3056	2289	5345
	3.5L	7100	1660	800	3750	3850	3094	2286	5380
MAX	3.5L	7550	2000	823	3750	4050	3111	2379	5490
	6.2L	7550	1880	879	3900	4050	3224	2457	5681
	5.0L	8200	2620	754	3750	4800	3132	2420	5552
HD Pkg.	3.5L	8200	2620	754	3750	4800	3150	2404	5554
	5.0L	7350	1570	714	4050	3850	3307	2409	5716
	3.5L	7350	1560	699	4050	3850	3322	2409	5731
MAX	3.5L	7700	1840	886	4050	4050	3322	2475	5797
	6.2L	7700	1730	871	4050	4050	3420	2484	5904
	5.0L	8200	2330	788	4050	4800	3346	2499	5845
HD Pkg.	3.5L	8200	2310	788	4050	4800	3361	2499	5860

(1) Load rating represents maximum allowable weight of people, cargo and body equipment and is reduced by optional equipment weight.

(2) OPT/ARC Weight is the maximum allowable weight for regular production options (OPT) and aftermarket equipment. Accessory Reserve Capacity (ARC) for models with standard equipment and the engine/transmission combination indicated.

(3) Gross Axle Weight Rating (GAWR) is determined by the rated capacity of the minimum component of the axle system (axle, computer-selected springs, wheels, tires) of a specific vehicle. Front and rear GAWRs will, in all cases, sum to a number equal to or greater than the GVWR for the particular vehicle. Maximum loaded vehicle (including passengers, equipment and payload) cannot exceed the GVWR.

(4) Vehicles equipped with 20" tires/wheels get 4050 lbs. RGAWR.

NOTE: Refer to pages 94 and 95 for Standard Powertrain/Chassis Equipment Specifications. See the Truck Payload section in the Source Book Appendices or on eSourceBook for optional equipment weights.