

SLIDE-IN Campers For F-Series Pickups



Slide-In Camper Installation

- Consult your camper manufacturer/dealer for details regarding proper installation of your slide-in camper
- A dimensionally stable block spacer is recommended between the headboard of the pickup box and the forward edge of the camper floor. Resting the spacer on the pickup box bed helps prevent movement and contact of the fully installed camper with the pickup box headboard or taillight rear pillars

Note: Be sure to measure your slide-in camper before attempting to install it onto the bed of the truck. Some campers may require a platform in the bed of the truck to make sure there is adequate clearance for both the box rails and cab roof of the truck.

Camper Center-Of-Gravity

- All Styleside pickups that qualify for slide-in camper bodies have camper center-of-gravity included on the Consumer Information Sheet in the glovebox
- Data is calculated for each individual truck, based on vehicle options
- If vehicle does not qualify for camper use, the Consumer Information Sheet states that the vehicle is not recommended for camper use, and no center-of-gravity data is shown

F-150 Heavy-Duty Payload Package (Option Code 627)

Increases GVWR to 8,200 pounds.

- LT245/75R17E BSW A/T tires (5)
- High-capacity 17" 7-lug steel wheels
- Heavy-duty shock absorbers
- Upgraded springs, radiator and auxiliary transmission oil cooler
- 9.75" gear set with 3.73 Limited Slip axle

Available on XL and XLT Regular Cab and SuperCab models with 8' box or Mid-Box Prep Package. Requires 5.4L gas engine and Max Trailer Tow Package.

F-250/F-350/F-450 Super Duty Camper Package (Option Code 471)

- Increased capacity front springs (2 Up [4x2] or 1 Up [4x4] upgrade over springs computer-selected based on options ordered. Not included if maximum springs already selected.)
- Rear stabilizer bar (SRW)
- Rear auxiliary springs (F-250)
- Slide-in camper certification

Use the chart below to select the proper F-SERIES PICKUP/CAMPER COMBINATION:

- Combined weight of vehicle, camper body, occupants and cargo must not exceed Gross Vehicle Weight Rating (GVWR)
- Heavy-Duty Payload Package (Option Code 627) required with F-150
- Camper Package (Option Code 471) required with F-250/F-350/F-450 Super Duty
- Cargo Weight Rating shown in chart is maximum allowable, assuming weight of a base vehicle with required camper option content and a 150-lb. passenger at each available seating position
- Ratings also assume weight of engine and standard transmission. Cargo Weight Rating shown must be further reduced by weight of transmission upgrade and any other options. Option weights and center-of-gravity information are available on the Ford Pickup Truck Consumer Information Sheet

If you intend to pull a trailer in addition to carrying your camper, see the F-Series Pickup Trailer Towing Selector charts on pages 18-20.

MAXIMUM CARGO WEIGHT WITH SLIDE-IN CAMPER (WITH MINIMUM EQUIPMENT)

Note: The following chart lists GVWRs and Maximum Cargo Weights by engine for each approved pickup model: 5.4L V8, 6.8L V10 and 6.4L Turbo Diesel V8.

Model	Wheelbase	GVWR (Lbs.)			Maximum Cargo Weight Rating (Lbs.)		
		5.4L	6.8L	6.4L	5.4L Std./Opt.†	6.8L Std./Opt.†	6.4L Std./Opt.†
F-150 (1)							
4x2 Reg. Cab	144.5"	8,200	-	-	2,627/ -	- / -	- / -
4x2 SuperCab	163.0"	8,200	-	-	1,795/ -	- / -	- / -
4x4 Reg. Cab	144.5"	8,200	-	-	2,326/ -	- / -	- / -
4x4 SuperCab	163.0"	8,200	-	-	1,491/ -	- / -	- / -
F-250 Super Duty (2)							
4x2 Reg. Cab	137.0"	8,800	9,000	9,400	2,722/ -	2,789/ -	2,407/ -
4x2 SuperCab	141.8"	9,000	9,200	9,600	2,254/ -	2,321/ -	1,876/ -
4x2 SuperCab	158.0"	9,200	9,400	9,800	2,300/ -	2,365/ -	1,952/ -
4x2 Crew Cab	156.2"	9,200	9,400	9,800	2,244/ -	2,316/ -	1,903/ -
4x2 Crew Cab	172.4"	9,400	9,600	10,000	2,325/ -	2,392/ -	1,979/ -
4x4 Reg. Cab	137.0"	9,000	9,200	9,600	2,502/ -	2,569/ -	2,171/ -
4x4 SuperCab	141.8"	9,200	9,400	9,800	2,033/ -	2,100/ -	1,640/ -
4x4 SuperCab	158.0"	9,400	9,600	10,000	2,079/ -	2,146/ -	1,716/ -
4x4 Crew Cab	156.2"	9,400	9,600	10,000	2,017/ -	2,091/ -	1,661/ -
4x4 Crew Cab	172.4"	9,600	9,800	10,000	2,105/ -	2,173/ -	1,543/ -
F-350 Super Duty (2)							
4x2 SRW Reg. Cab(3)	137.0"	-	-	10,200*	- / -	- / -	3,144/2,944
4x2 SRW SuperCab(3)	141.8"	-	-	10,400*	- / -	- / -	2,645/2,245
4x2 SRW SuperCab(3)	158.0"	10,100*	10,200*	10,600*	3,136/3,036	3,101/2,901	2,720/2,120
4x2 SRW Crew Cab(3)	156.2"	10,100*	10,200*	10,600*	3,080/2,980	3,052/2,852	2,672/2,072
4x2 SRW Crew Cab(3)	172.4"	10,200*	10,400*	10,800*	3,060/2,860	3,128/2,728	2,747/1,947
4x2 SRW Reg. Cab(4)	137.0"	10,100*	10,100*	10,600*	3,852/3,752	3,721/3,621	3,439/2,839
4x2 SRW SuperCab(4)	141.8"	10,100*	10,200*	10,800*	3,185/3,085	3,152/2,952	2,940/2,140
4x2 SRW SuperCab(4)	158.0"	10,400*	10,600*	11,000*	3,329/2,929	3,396/2,796	3,015/2,015
4x2 SRW Crew Cab(4)	156.2"	10,400*	10,600*	11,000*	3,275/2,875	3,347/2,747	2,967/1,967
4x2 SRW Crew Cab(4)	172.4"	10,600*	10,800*	11,200*	3,355/2,755	3,420/2,620	3,042/1,842
4x2 DRW Reg. Cab	137.0"	11,800	12,000	12,400	5,234/ -	5,303/ -	4,927/ -
4x2 DRW SuperCab	158.0"	12,200	12,400	12,800	4,810/ -	4,877/ -	4,503/ -
4x2 DRW Crew Cab	172.4"	12,400	12,600	13,000	4,837/ -	4,901/ -	4,530/ -
4x4 SRW Reg. Cab(3)	137.0"	10,100*	10,200*	10,600*	3,538/3,438	3,505/3,305	3,108/2,508
4x4 SRW SuperCab(3)	141.8"	10,200*	10,400*	10,800*	2,968/2,768	3,036/2,636	2,608/1,808
4x4 SRW SuperCab(3)	158.0"	10,400*	10,600*	11,000*	3,014/2,614	3,081/2,481	2,684/1,684
4x4 SRW Crew Cab(3)	156.2"	10,400*	10,600*	11,000*	2,953/2,553	3,026/2,426	2,629/1,629
4x4 SRW Crew Cab(3)	172.4"	10,600*	10,800*	11,200*	3,041/2,441	3,108/2,308	2,711/1,511
4x4 SRW Reg. Cab(4)	137.0"	10,400*	10,600*	11,000*	3,733/3,333	3,800/3,200	3,403/2,403
4x4 SRW SuperCab(4)	141.8"	10,600*	10,800*	11,200*	3,263/2,663	3,331/2,531	2,903/1,703
4x4 SRW SuperCab(4)	158.0"	10,800*	11,000*	11,400*	3,309/2,509	3,376/2,376	2,979/1,579
4x4 SRW Crew Cab(4)	156.2"	10,800*	11,000*	11,400*	3,248/2,448	3,321/2,321	2,924/1,524
4x4 SRW Crew Cab(4)	172.4"	11,000*	11,200*	11,500*	3,336/2,336	3,403/2,203	2,906/1,406
4x4 DRW Reg. Cab	137.0"	12,000	12,200	12,600	5,014/ -	5,082/ -	4,691/ -
4x4 DRW SuperCab	158.0"	12,400	12,600	13,000	4,591/ -	4,658/ -	4,267/ -
4x4 DRW Crew Cab	172.4"	12,400	12,600	13,000	4,418/ -	4,485/ -	4,094/ -
F-450 Super Duty (2)							
4x2 DRW Crew Cab	172.4"	-	-	14,500	- / -	- / -	5,367/ -
4x4 DRW Crew Cab	172.4"	-	-	14,500	- / -	- / -	5,019/ -

(1) Requires Heavy-Duty Payload Package option. (2) Requires Camper Package option.

(3) 17" tires and wheels with XL trim. (4) 18" tires and wheels with all trims.

*10,000 pounds with optional 10,000 GVWR Package. † With 10,000 GVWR Package.